

HeartSine® samaritan® PAD 350P/360P

Connected AEDs

**Semi-Automatic/Fully Automatic Public Access Defibrillators
with Integrated Wi-Fi® Connectivity**

Data sheet

A Ready AED. So simple.

Sudden cardiac arrest strikes with little time to react and even less time to think. This means an Automated External Defibrillator (AED) must be close at hand, easy to use and ready to shock. Designed for simplicity, HeartSine samaritan PAD 350P and 360P Connected AEDs offer key features that help ensure readiness:

- Simplified readiness monitoring
- Integrated Wi-Fi® connectivity
- AED program management
- Low cost of ownership

Readiness made easy

- **LIFELINKcentral AED Program Manager**
Monitors AED programs by tracking AED readiness status, Pad-Pak™ expirations, CPR/AED training certificates and more.
- **Integrated connectivity**
Communicates via Wi-Fi with LIFELINKcentral™ AED Program Manager to enable AEDs to be managed across a single or multiple locations.



Made for you

- **Real-time CPR coaching**
Easy to understand visual and voice prompts guide the rescuer through the entire resuscitation process, including CPR—a key link in the chain of survival.
- **One- or two-button operation**
With just an ON/OFF button (and the SHOCK button on the SAM 350P), offers a simple, straightforward operation.
- **Automatic shock delivery / Motion detection**
After analysing heart rhythm, automatically delivers a shock (if needed), eliminating the need for the rescuer to push a shock button (SAM 360P).
- **Portable and lightweight**
Most portable AED offered by a leading manufacturer with its light weight (1.285 kg) and compact footprint.
- **Clinically validated technology**
Proprietary electrode technology and SCOPE™ biphasic technology, a low energy escalating waveform, that automatically adjusts for differences in patient impedance.
- **Highest level of protection against dust and water**
Offers unmatched ruggedness with its high IP56 rating.



Simple to own

- **Two parts, one expiration date**
The innovative Pad-Pak, an integrated battery and electrode single-use cartridge with one expiration date, offers one simple maintenance change every four years.
- **Low cost of ownership**
Shelf life of four years means that the Pad-Pak offers significant savings over other defibrillators that require separate battery and electrode replacements.
- **8-year Warranty**
AED is backed by an 8-year warranty.

Specifications

Defibrillator

Waveform: Self-Compensating Output Pulse Envelope (SCOPE) optimised biphasic escalating waveform compensates energy, slope and duration for patient impedance

Patient analysis system

Method: Evaluates patient's ECG, signal quality, electrode contact integrity and patient impedance to determine if defibrillation is required

Sensitivity/Specificity: Meets IEC/EN 60601-2-4

Impedance range: 20-230 ohms

Energy selection

Pad-Pak shock:

Shock 1: 150J

Shock 2: 150J

Shock 3: 200J

Pediatric-Pak™:

Shock 1: 50J

Shock 2: 50J

Shock 3: 50J

Charge time (typical):

150J in < 8 seconds,

200J in < 12 seconds

Environmental

Operating/Standby temperature:

0°C to 50°C (32°F to 122°F)

Transportation temperature:

-10°C to 50°C (14°F to 122°F) for up to two days. If the device has been stored below 0°C (32°F), it should be returned to an ambient temperature of between 0°C to 50°C (32°F to 122°F) for at least 24 hours before use.

Relative humidity:

5% to 95% non-condensing

Water resistance:

IEC 60529/ EN60529 IPX6 with electrodes connected and battery installed

Dust resistance:

IEC 60529/ EN60529 IP5X with electrodes connected and battery installed

Enclosure:

IEC/EN 60529 IP56

Altitude:

0 to 4 575 metres (0 to 15 000 feet)

Shock:

MIL STD 810F Method 516.5, Procedure 1 (40 G's)

Vibration: MIL STD 810F Method 514.5, Procedure 1

Category 4 Truck Transportation – US Highways

Category 7 Aircraft – Jet 737 & General Aviation

EMC: IEC/EN 60601-1-2

Radiated emissions: IEC/EN 55011

Electrostatic discharge:

IEC/EN 61000-4-2 (8 kV)

RF immunity:

IEC/EN 61000-4-3 80MHz-2.5 GHz, (10 V/m)

Magnetic field immunity:

IEC/EN 61000-4-8 (3 A/m)

Aircraft: RTCA/DO-160G, Section 21 (Category M)

RTCA/DO-227 (ETSO-C142a)

Falling height: 1 metre (3.3 feet)

Physical characteristics

With Pad-Pak inserted and HeartSine Gateway™, with batteries, attached:

Size:

23.4 cm x 18.4 cm x 4.8 cm
(9.21 in x 7.25 in x 1.9 in)

Weight: 1.285 kg (2.83 lb)

Accessories

Pad-Pak Electrode and Battery Cartridge

Shelf life/Standby life:

See the expiration date on the Pad-Pak/ Pediatric-Pak (4 years from manufacture date)

Weight: 0.2 kg (0.44 lb)

Size:

10 cm x 13.3 cm x 2.4 cm
(3.93 in x 5.24 in x 0.94 in)

Battery type: Disposable single-use combined battery and defibrillation electrode cartridge (lithium manganese dioxide (LiMnO₂) 18V)

Battery capacity (new):

> 60 shocks at 200J or
6 hours of continuous monitoring

Electrodes: Disposable defibrillation pads are supplied as standard with each device

Electrode placement: Anterior - lateral (Adult)

Anterior - posterior or Anterior - lateral (Pediatric)

Electrode active area: 100 cm² (15 in²)

Electrode cable length: 1 metre (3.3 feet)

Aircraft safety test (ETSO-certified Pad-Pak): RTCA/DO-227 (ETSO-C142a)

HeartSine Gateway Battery

Type: CR123A 3V, Non-rechargeable

Type number: 6205

Designation IEC: CR 17345

Weight (per battery): 17g

Quantity: Four

System: Lithium Manganese Dioxide / Organic Electrolyte

UL recognition: MH 13654 (N)

Nominal voltage (per battery): 3V

Typical capacity load:

100 Ohm, at 20°C, 1550 mAh down to 2V

Volume: 7 ccm (0.43 in³)

Data storage

Memory type: Internal memory

Memory storage: 90 minutes of ECG (full disclosure) and event/incident recording

Review: Custom USB data cable (optional) directly connected to PC with Saver EVO™ Windows®-based data review software

Materials used

Defibrillator housing / HeartSine Gateway: ABS, Santoprene

Electrodes: Hydrogel, Silver, Aluminium and Polyester

Warranty

AED: 8-year limited warranty

HeartSine Gateway: 2-year limited warranty

Communications

Wireless 802.11 b/g/n data transfer to LIFELINKcentral AED Program Manager or LIFENET System. USB connection to Saver EVO software through Micro USB port

For further information contact us at heartsinesupport@stryker.com or visit our website at www.heartsine.com.

EMEA/APAC

HeartSine Technologies, Ltd.
203 Airport Road West
Belfast, Northern Ireland
BT3 9ED
Tel: +44 28 9093 9400
Fax: +44 28 9093 9401



U.S./Americas

HeartSine Technologies LLC
121 Friends Lane, Suite 400
Newtown, PA 18940
Toll Free: (866) 478 7463
Tel: +1 215 860 8100
Fax: +1 215 860 8192

The HeartSine products described in this brochure meet the European Medical Directive requirement.



UL Classified. See complete marking on product.



H009-043-003-0 Intl

© 2018 HeartSine Technologies LLC. All rights reserved.